

Sheave with Ball Bearings, Rigging



Product information

Self-lubricating cast sheaves are often applied in lifting, luffing and wire rope routing with intensive operating cycles. The groove opening angle was carefully designed to reduce potential twist resulting from fleet angles. In combination with the self-lubricating effect, the wire rope in your system will last longer. The latter was proved in recent research, in which several sheave materials were compared in terms of their effect on rope twist.

- Different shaft sizes possible.
- Groove may be adjusted to other wire rope diameters.

Part code	Rope Ø range mm	Bearing	Material	Bearing	øD2 mm	øG mm	R mm	øD1 mm	øD3 mm	E mm	F mm	Weight kg
10.35311006002	8	Ball bearing	GGG-60	2x6002-RS	80	15	4.5	100	88	18	20	0.7
10.35311256002	10	Ball bearing	GGG-60	2x60/22-RS	105	22	5.5	125	115	23	27.5	1.5
10.35311506002	12	Ball bearing	GGG-60	2x6206-RS	120	30	6.5	150	132	36	40	3
10.35312006002	14	Ball bearing	GGG-60	2x6206-RS	165	30	7.5	200	179	36	40	4.5
10.35312506002	18	Ball bearing	GGG-60	2x6207-RS	210	35	9.5	250	228	40	45	8
10.35313006002	20	Ball bearing	GGG-60	2x6208-RS	255	40	11	300	275	45	50	12
10.35313507002	22	Ball bearing	GGG-70	2x6209-RS	305	45	12	350	327	45	50	17
10.35314007002	24	Ball bearing	GGG-70	2x6210-RS	345	50	13	400	369	55	60	24

Blueprint

