

Tendeur oeil/oeil

Informations du produit



Informations générales :

- Galvanisé.
- Equipé de boulons écrous.
- Charge d'essai 2,5 x CMU.
- Chargement en ligne droite.
- Acier de haute qualité.
- Charge de rupture = 5 x CMU.

Réf.	CMU	Dia. filetage X longueur int. corps mm	L min. mm	L max. mm.	A mm	J mm	K mm	L mm	Poids
11.51400250422	0,23	6.35 x 102	198	300	121	6	9	20	0,12
11.51400310422	0,36	7.94 x 114	230	344	138	8	11	24	0,2
11.51400330622	0,54	9.53 x 152	291	444	181	9	13	28	0,34
11.51400500622	1	12.7 x 152	332	510	191	11	18	37	0,7
11.51400500922	1	12.7 x 229	409	614	266	11	18	37	0,77
11.51400501222	1	12.7 x 305	485	815	343	11	18	37	0,97
11.51400620922	1,59	15.9 x 229	450	655	276	13	22	44	1,32
11.51400620622	1,59	15.9 x 152	373	557	200	13	22	44	1,49

11.51400621222	1,59	15.9 x 305	525	862	353	13	22	44	1,55
11.51400750622	2,36	19.1 x 152	416	607	210	16	25	53	1,72
11.51400750922	2,36	19.1 x 229	492	697	286	16	25	53	1,92
11.514.0751222	2,36	19.1 x 305	568	911	362	16	25	53	2,49
11.51400751822	2,36	19.1 x 457	721	1 216	514	16	25	53	3,26
11.51400871222	3,27	22.2 x 305	592	942	370	19	32	60	3,27
11.51400871822	3,27	22.2 x 457	745	1 246	523	19	32	60	4,51
11.51401000622	4,54	25.4 x 152	507	710	228	23	36	76	4,1
11.51401001222	4,54	25.4 x 305	660	1 015	380	23	36	76	5,22
11.51401001822	4,54	25.4 x 457	812	1 320	532	23	36	76	6,35
11.51401002422	4,54	25.4 x 610	964	1 625	685	23	36	76	7,82
11.51401251222	6,89	31.8 x 305	719	1 087	384	29	46	90	8,62
11.51401251822	6,89	31.8 x 457	871	1 392	537	29	46	90	10,4
11.51401252422	6,89	31.8 x 610	1 024	1 697	689	29	46	90	12,2
11.51401501222	9,71	38.1 x 305	775	1 156	400	32	54	103	12,5
11.51401501822	9,71	38.1 x 457	927	1 461	553	32	54	103	14,1
11.51401502422	9,71	38.1 x 610	1 080	1 765	705	32	54	103	17
11.51401751822	12,7	44.5 x 457	1 000	1 457	568	38	60	117	23,8
11.51401752422	12,7	44.5 x 610	1 153	1 762	721	38	60	117	26,3
11.51402002422	16,8	51.0 x 610	1 313	1 923	738	45	68	146	8,7
11.51402502422	27,2	63.5 x 610	1 387	1 997	789	51	79	165	65
11.51402752422	34	70 x 610	1 448	2 057	788	57	82	177	88

Dimensions

