

4023000 / Clapets à double effet

Informations du produit



Informations générales : clapets à double effet

Caractéristiques et avantages :

- Pour outils à double effet
- Le levier s'arrête à chaque position
- Avec soupape anti-retour à régulation de pression pour sécurisation de la charge
- Valve 3 positions / 4 voies
- Raccordement 3/8" NPT femelle (2x)

Réf.	Modèle	Description
100.172.051	M 304	• For assembly on the variump underneath adouble-acting valve (M 322, M 323, M324 orM 325)• This valve makes it possible to drive both singleand double acting tools with just one pump• Switch with A + B function (double-acting) or A(single-acting)
100.181.311	M 311	• Suitable for single-acting tools• Handle stops in each position• 3-position, 3-way Valve• Not in combination with a vari pump model(name) starting with 18 W• Connection 3/8" NPT female thread (2x)
100.181.322	M 322	• Suitable for double-acting tools• Handle stops in each position• With pressure-controlled non-return valves forsecuring the load• 3-position 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.323	M 323	• Suitable for double-acting tools• Handle with dead man's function, automaticallygoes to "O" position• With pressure-controlled non-return valves forsecuring the load• 3-position, 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.324	M 324	• Only suitable in combination with EC-versionVari pumps. Contact our sales department foradditional information• Suitable for double-acting tools. Valve withelectromagnetic control (24 VDC)• With pressure-controlled non-return valves forsecuring the load• 3-position, 4-way valve• Connection: 3/8" NPT female (2x)• Remote control, art no 100.151.060 (to beordered separately)• 4 buttons (on, off, lift and lower)
100.182.175	VM 43 L	• Suitable for double-acting tools• Handle stops in each position• With pressure controlled non-return valves forsecuring the load• 3-position 4-way valve• Connection: 3/8" NPT female (2x)