

## 4023000 / Clapets à double effet

### Informations du produit



**Informations générales :** clapets à double effet

**Caractéristiques et avantages :**

- Pour outils à double effet
- Le levier s'arrête à chaque position
- Avec soupape anti-retour à régulation de pression pour sécurisation de la charge
- Valve 3 positions / 4 voies
- Raccordement 3/8" NPT femelle (2x)

Réf.	Modèle	Description
100.172.051	M 304	• For assembly on the varipump underneath a double-acting valve (M 322, M 323, M324 or M 325)• This valve makes it possible to drive both single and double acting tools with just one pump• Switch with A + B function (double-acting) or A (single-acting)
100.181.311	M 311	• Suitable for single-acting tools• Handle stops in each position• 3-position, 3-way Valve• Not in combination with a vari pump model (name) starting with 18 W• Connection 3/8" NPT female thread (2x)
100.181.322	M 322	• Suitable for double-acting tools• Handle stops in each position• With pressure-controlled non-return valves for securing the load• 3-position 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.323	M 323	• Suitable for double-acting tools• Handle with dead man's function, automatically goes to "O" position• With pressure-controlled non-return valves for securing the load• 3-position, 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.324	M 324	• Only suitable in combination with EC-version Vari pumps. Contact our sales department for additional information• Suitable for double-acting tools. Valve with electromagnetic control (24 VDC)• With pressure-controlled non-return valves for securing the load• 3-position, 4-way valve• Connection: 3/8" NPT female (2x)• Remote control, art no 100.151.060 (to be ordered separately)• 4 buttons (on, off, lift and lower)
100.182.175	VM 43 L	• Suitable for double-acting tools• Handle stops in each position• With pressure controlled non-return valves for securing the load• 3-position 4-way valve• Connection: 3/8" NPT female (2x)