

Bedieningskleppen

Productinformatie



Algemeen: Bedieningskleppen

Kenmerken en voordelen:

- Geschikt voor dubbelwerkende gereedschappen
- Hendel met arretering in elke stand
- Voorzien van drukgestuurde terugslagkleppen, voor vergrendeling van de last
- 3-standen 4-wegklep
- Aansluiting: 3/8" NPT inwendig (2x)

Artikelnr. Type	Omschrijving
100.172.051M 304	• For assembly on the varipump underneath adouble-acting valve (M 322, M 323, M324 orM 325)• This valve makes it possible to drive both singleand double acting tools with just one pump• Switch with A + B function (double-acting) or A(single-acting)
100.181.311M 311	• Suitable for single-acting tools• Handle stops in each position• 3-position, 3-way Valve• Not in combination with a vari pump model(name) starting with 18 W• Connection 3/8" NPT female thread (2x)
100.181.322M 322	• Suitable for double-acting tools• Handle stops in each position• With pressure-controlled non-return valves forsecuring the load• 3-position 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.323M 323	• Suitable for double-acting tools• Handle with dead man's function, automaticallygoes to "O" position• With pressure-controlled non-return valves forsecuring the load• 3-position, 4-way Valve• Connection: 3/8" NPT female (2x)
100.181.324M 324	• Only suitable in combination with EC-versionVari pumps. Contact our sales department foradditional information• Suitable for double-acting tools. Valve withelectromagnetic control (24 VDC)• With pressure-controlled non-return valves forsecuring the load• 3-position, 4-way valve• Connection: 3/8" NPT female (2x)• Remote control, art no 100.151.060 (to beordered separately)• 4 buttons (on, off, lift and lower)
100.182.175 VM 43 L	• Suitable for double-acting tools• Handle stops in each position• With pressure controlled non-return valves forsecuring the load• 3-position 4-way valve• Connection: 3/8" NPT female (2x)